



Шпильки без резьбы (UD)

ISO13918

L2 – высота после приварки

Для дуговой приварки с керамическим кольцом или защитным газом с возбуждением дуги размыканием цепи

| d1 | L2 | h4 | d3 | Арт. | Масса кг/100 шт | Керамическое кольцо | Зажимной патрон | Наконечник кольца | Опора |
|------|---------------|----|------|--------------|-----------------|---------------------|-----------------|-------------------|-----------------------------------|
| 6 | 15 | 4 | 8,5 | 005-0001-001 | 0,37 | UF 6 | 350-0004-000 | 355-0002-000 | 360-0101-000 K 360-0013-000 SK |
| | 20 | | | 005-0002-001 | 0,48 | | 350-0005-000 | | |
| | 25 | | | 005-0003-001 | 0,59 | | | | |
| | 30 | | | 005-0004-001 | 0,7 | | | | |
| | 35 | | | 005-0005-001 | 0,81 | | | | |
| | 40 | | | 005-0006-001 | 0,92 | | | | |
| | 50 | | | 005-0008-001 | 1,14 | | | | |
| | 60 | | | 005-0010-001 | 1,37 | | | | |
| 8 | 15 | 4 | 11 | 005-0040-001 | 0,66 | UF 8 | 350-0006-000 | 355-0003-000 | 360-0101-000 K 360-0013-000 SK |
| | 20 | | | 005-0041-001 | 0,85 | | 350-0007-000 | | |
| | 25 | | | 005-0043-001 | 1,05 | | | | |
| | 30 | | | 005-0044-001 | 1,25 | | | | |
| | 35 | | | 005-0045-001 | 1,45 | | | | |
| | 40 | | | 005-0047-001 | 1,64 | | | | |
| | 50 | | | 005-0049-001 | 2,04 | | | | |
| | 60 | | | 005-0052-001 | 2,43 | | | | |
| | 80 | | | 005-0056-001 | 3,22 | | | | |
| | 100 | | | 005-0060-001 | 4,01 | | | | |
| 10 | 20 | 4 | 13 | 005-0110-001 | 1,34 | UF 10 | 350-0008-000 | 355-0004-000 | 360-0101-000 K 360-0013-000 SK |
| | 25 | | | 005-0111-001 | 1,65 | | 350-0009-000 | | |
| | 30 | | | 005-0112-001 | 1,96 | | | | |
| | 35 | | | 005-0113-001 | 2,27 | | | | |
| | 40 | | | 005-0114-001 | 2,58 | | | | |
| | 50 | | | 005-0116-001 | 3,19 | | | | |
| | 55 | | | 005-0117-001 | 3,26 | | | | |
| | 60 | | | 005-0118-001 | 3,81 | | | | |
| | 70 | | | 005-0120-001 | 4,42 | | | | |
| | 80 | | | 005-0122-001 | 5,04 | | | | |
| 12 | 25 | 5 | 16 | 005-0173-001 | 2,39 | UF 12 | 350-0010-000 | 355-0005-000 | 360-0101-000 K 360-0013-000 SK |
| | 30 | | | 005-0174-001 | 2,84 | | 350-0011-000 | | |
| | 35 | | | 005-0175-001 | 3,28 | | | | |
| | 40 | | | 005-0176-001 | 3,72 | | | | |
| | 45 | | | 005-0177-001 | 4,17 | | | | |
| | 50 | | | 005-0178-001 | 4,61 | | | | |
| | 60 | | | 005-0180-001 | 5,5 | | | | |
| | 70 | | | 005-0182-001 | 6,39 | | | | |
| | 80 | | | 005-0184-001 | 7,27 | | | | |
| | 100 | | | 005-0188-001 | 9,05 | | | | |
| 14,6 | ≥ 20 ≤ 100 | 6 | 18.5 | | | RF 16 | 350-0014-000 | | |
| 16 | ≥ 20 ≤ 100 | 7 | 21 | | | UF 16 | 350-0016-000 | 355-0007-000 | 360-0103-000 |